

FullPOWER EVO

TCAVB 2335÷21505

TCAVT-TCAVQ

2345÷21565

Cooling capacity: 336.6X÷1564.1 kW



√ **High energy efficiency chillers in R513A and R134a**

√ **Extended operating limits**

√ **Linear capacity control (25-100%)**

√ **Wide range of accessories**

√ **Integrated MASTER/SLAVE control**



Web code: (TCAVTL, TCAVQL): FPE23 (TCAVBL): FP023 (TCAVTZ, TCAVQZ): FPE21 (TCAVBZ): FP021

Packaged air-cooled water chillers with axial fans. Series with semi-hermetic screw compressors and R513A or R134a refrigerant gas.

Construction features

- Compressor: high energy efficiency semi-hermetic screw compressor with linear capacity control (25-100%). Star-delta limited start-up and complete with integral protection, casing heater and refrigerant gas outlet piping shut-off valve.
- Water side heat exchanger: dry expansion shell and tube exchanger with counterflow heat exchange, complete with closed cell polyurethane foam rubber insulation, water flow differential pressure switch and Victaulic fittings.
- Air side heat exchanger: with micro-channels.
- Fan: external rotor axial type electric fans equipped with internal thermal protection, accident protection grilles and proportional electronic device for continuous fan rotation speed adjustment.
- Control: microprocessor electronic control.
- Structure: made of galvanised and painted steel plate with polyester powder coating.
- The unit is also complete with:
 - display of cooling circuit high/low pressure;
 - electronic expansion valve;
 - clock board;
 - Master/Slave control up to 4 units in parallel;
 - control of Variable Primary Flow (VPF_R).

Versions

- B - Standard efficiency version (TCAVBL-TCAVBZ).
- T - High efficiency version with oversized condensing section

(TCAVTL-TCAVTZ).

- Q - Super-silenced version complete with soundproof compressor technical compartment, reduced speed fans and oversized condensing section (TCAVQL-TCAVQZ).

Models

- TCAVBL: standard efficiency unit designed for cooling only with R513A gas.
- TCAVTL: high efficiency unit designed for cooling only with R513A gas.
- TCAVQL: super silenced unit designed for cooling only with R513A gas.
- TCAVBZ: standard efficiency unit designed for cooling only with R134a gas.
- TCAVTZ: high efficiency unit designed for cooling only with R134a gas.
- TCAVQZ: super silenced unit designed for cooling only with R134a gas.

Factory fitted accessories

- PUMP with single or double electric pump, one of which automatic in standby. The electric pumps are available in the low or high head versions.
- Inverter pump control for unit start-up.
- Desuperheater.

- 100% heat recovery unit.
- Condensing control with fans with EC motor
- Condensing control with over-pressure fans (B-T versions only)
- Power factor correction capacitors ($\cos\phi > 0.94$).
- Compressor circuit breaker switches.
- Electro-mechanical flow switch.
- Oil level sensor.
- Forced limit of power consumption.
- Forced noise limit.
- Energy parameter measuring device.
- Soft starter.
- Soundproofed compressor box.
- Cooling circuit intake valves.
- Refrigerant leak detector.
- Cooling circuit high and low pressure gauges.
- Double safety valves.
- Coil protection nets or buffer panels
- Microchannel coils with E-coating treatment, copper/aluminium, copper/copper, pre-painted copper/aluminium
- Control of min/max power supply voltage.
- Digital input for double set-point.
- 4-20 mA analogue signal for shifting set-point.
- Evaporator antifreeze heater, electrical panel, electric pumps and heat exchangers for heat recovery if applicable.
- Low temperature water production.
- Interfaces for serial communication with other devices.
- Colour touch user keypad (fitted on the machine or remotely) with 7" display
- Spring anti-vibration mounts
- Protective packaging

Separately supplied accessories

- Remote keypad with display.
- Thermostat with display.
- Rhoss supervisors for unit monitoring and remote management.
- Rhoss sequencer for integrated management of multiple chillers.

Technical Data

TCAVBL MODEL		2335	2365	2405	2465	2515	2565	2645	2705
① Nominal cooling capacity	kW	333,6	370,6	406,5	464,5	520,4	565,4	650,4	708,4
① E.E.R.		3	2,91	2,85	3	2,89	2,84	2,95	2,9
① Absorbed power	kW	111,2	127,4	142,6	154,8	180,1	199,1	220,5	244,3
TCAVBL MODEL		2335	2365	2405	2465	2515	2565	2645	2705
② Sound pressure	dB(A)	65	65	66	66	66	66	66,5	66,5
③ Sound power	dB(A)	97	97	98	98	98	98	99	99
Screw compressor/steps	n.	2/ CONTINUOUS LINEAR REGULATION (25-100%)							
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2335	2365	2405	2465	2515	2565	2645	2705
L - Width	mm	3740	3740	3740	4840	4840	4840	5990	5990
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVBL weight	kg	2760	2770	2790	3220	3780	3990	4330	4360
TCAVTL-TCAVQL MODEL		2345	2385	2425	2475	2525	2585	2655	2715
① Nominal cooling capacity	kW	343,6	383,6	427,6	478,5	532,4	583,4	664,4	719,4
① Nominal cooling capacity	kW	333,7	372,6	410,6	474,5	511,5	560,4	638,5	698,4
① E.E.R.		3,24	3,21	3,19	3,24	3,2	3,19	3,27	3,23
① E.E.R.		3,15	3,1	3,02	3,11	3,03	2,94	3,03	2,93
① Absorbed power	kW	106	119,5	134	147,7	166,4	182,9	203,2	222,7
① Absorbed power	kW	105,9	120,2	136	152,6	168,8	190,6	210,7	238,4
TCAVTL-TCAVQL MODEL		2345	2385	2425	2475	2525	2585	2655	2715
② TCAVTL Sound pressure	dB(A)	65,5	65,5	65,5	65,5	65,5	66,5	66,5	66,5
② TCAVQL Sound pressure	dB(A)	56,5	56,5	56,5	56,5	56,5	57,5	57,5	57,5
③ TCAVTL Sound power	dB(A)	98	98	98	98	98	99	99	99
③ TCAVQL Sound power	dB(A)	89	89	89	89	89	90	90	90
Screw compressor/steps	n.	2/ CONTINUOUS LINEAR REGULATION (25-100%)							
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2345	2385	2425	2475	2525	2585	2655	2715
L - Width	mm	4840	4840	4840	5990	5990	5990	7150	7150
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVTL weight	kg	3120	3125	3150	3515	4270	4300	4810	4840
① TCAVQL weight	kg	3395	3400	3425	3790	4650	4680	5210	5240
SEASONAL ENERGY PERFORMANCE									
TCAVBL MODEL SEASONAL PERFORMANCE IN COOLING MODE		2335	2365	2405	2465	2515	2565	2645	2705
① Pdesignc (EN 14825)	kW	333,6	370,6	406,5	464,5	520,4	565,4	650,4	708,4
① SEER (EN 14825)		4,62	4,59	4,57	4,64	4,58	4,55	4,62	4,59
② ηs,c	%	182	181	180	183	180	179	182	181
TCAVTL MODEL SEASONAL PERFORMANCE IN COOLING MODE		2345	2385	2425	2475	2525	2585	2655	2715
① Pdesignc (EN 14825)	kW	343,6	383,6	427,6	478,5	532,4	583,4	664,4	719,4
① SEER (EN 14825)		4,8	4,72	4,71	4,77	4,71	4,72	4,77	4,76
② ηs,c	%	189	186	185	188	185	186	188	187
TCAVQL MODEL SEASONAL PERFORMANCE IN COOLING MODE		2345	2385	2425	2475	2525	2585	2655	2715
① Pdesignc (EN 14825)	kW	333,7	372,6	410,6	474,5	511,5	560,4	638,5	698,4
① SEER (EN 14825)		4,73	4,63	4,61	4,72	4,68	4,61	4,69	4,67
② ηs,c	%	186	182	181	186	184	181	185	184
TCAVBZ MODEL		2335	2365	2405	2465	2515	2565	2645	2705
① Nominal cooling capacity	kW	334,6	371,6	408,5	466,5	522,3	567,4	653,4	711,4
① E.E.R.		3,09	2,98	2,93	3,07	2,97	2,9	3,03	2,97
① Absorbed power	kW	108,3	124,7	139,4	152	175,9	195,7	215,6	239,5
TCAVBZ MODEL		2335	2365	2405	2465	2515	2565	2645	2705
② Sound pressure	dB(A)	65	65	66	66	66	66	66,5	66,5
③ Sound power	dB(A)	97	97	98	98	98	98	99	99
Screw compressor/steps	n.	2/ CONTINUOUS LINEAR REGULATION (25-100%)							
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2335	2365	2405	2465	2515	2565	2645	2705
L - Width	mm	3740	3740	3740	4840	4840	4840	5990	5990
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVBZ weight	kg	2760	2770	2790	3220	3780	3990	4330	4360
TCAVTZ-TCAVQZ MODEL		2345	2385	2425	2475	2525	2585	2655	2715
① Nominal cooling capacity	kW	344,6	384,6	429,6	480,5	534,4	585,4	667,4	722,4
① Nominal cooling capacity	kW	334,7	373,6	412,6	476,5	513,5	562,4	641,5	701,4
① E.E.R.		3,34	3,3	3,27	3,32	3,3	3,28	3,35	3,32
① E.E.R.		3,25	3,18	3,1	3,18	3,11	3,02	3,11	3
① Absorbed power	kW	103,2	116,5	131,4	144,7	161,9	178,5	199,2	217,6
① Absorbed power	kW	103	117,5	133,1	149,8	165,1	186,2	206,3	233,8

TCAVTZ-TCAVQZ MODEL		2345	2385	2425	2475	2525	2585	2655	2715
② TCAVTZ Sound pressure	dB(A)	65,5	65,5	65,5	65,5	65,5	66,5	66,5	66,5
② TCAVQZ Sound pressure	dB(A)	56,5	56,5	56,5	56,5	56,5	57,5	57,5	57,5
③ TCAVTZ Sound power	dB(A)	98	98	98	98	98	99	99	99
③ TCAVQZ Sound power	dB(A)	89	89	89	89	89	90	90	90
2/ CONTINUOUS LINEAR REGULATION (25-100%)									
Screw compressor/steps	n.								
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2345	2385	2425	2475	2525	2585	2655	2715
L - Width	mm	4840	4840	4840	5990	5990	5990	7150	7150
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVTZ weight	kg	3120	3125	3150	3515	4270	4300	4810	4840
① TCAVQZ weight	kg	3395	3400	3425	3790	4650	4680	5210	5240
SEASONAL ENERGY PERFORMANCE									
TCAVBZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		2335	2365	2405	2465	2515	2565	2645	2705
① Pdesignc (EN 14825)	kW	334,6	371,6	408,5	466,5	522,3	567,4	653,4	711,4
① SEER (EN 14825)		4,68	4,63	4,6	4,67	4,62	4,58	4,66	4,62
② ηs,c	%	184	182	181	184	182	180	183	182
TCAVTZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		2345	2385	2425	2475	2525	2585	2655	2715
① Pdesignc (EN 14825)	kW	344,6	384,6	429,6	480,5	534,4	585,4	667,4	722,4
① SEER (EN 14825)		4,83	4,77	4,76	4,82	4,76	4,76	4,82	4,81
② ηs,c	%	190	188	187	190	187	187	190	189
TCAVQZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		2345	2385	2425	2475	2525	2585	2655	2715
① Pdesignc (EN 14825)	kW	334,7	373,6	412,6	476,5	513,5	562,4	641,5	701,4
① SEER (EN 14825)		4,78	4,68	4,65	4,75	4,71	4,66	4,73	4,72
② ηs,c	%	188	184	183	187	186	183	186	186
TCAVBL MODEL		2755	2805	2865	2935	2995	21075	21115	21275
① Nominal cooling capacity	kW	758,4	799,4	865,3	944,3	994,2	1081,3	1121,2	1287,1
① E.E.R.		2,87	2,96	2,88	2,97	2,91	3,03	2,93	3,04
① Absorbed power	kW	264,3	270,1	300,5	317,9	341,6	356,9	382,7	423,4
TCAVBL MODEL		2755	2805	2865	2935	2995	21075	21115	21275
② Sound pressure	dB(A)	67,5	67,5	68	68	68	69	69	69
③ Sound power	dB(A)	100	100	101	101	101	102	102	102
Screw compressor/steps	n.								
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2755	2805	2865	2935	2995	21075	21115	21275
L - Width	mm	5990	7150	7150	8250	8250	9350	9350	10450
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVBL weight	kg	4390	5400	5820	6210	6270	6780	6800	7180
TCAVTL-TCAVQL MODEL		2765	2815	2885	2955	21025	21105	21175	21335
① Nominal cooling capacity	kW	772,3	820,4	887,3	964,3	1029,3	1116,2	1176,2	1327,1
① Nominal cooling capacity	kW	749,3	788,4	847,3	926,4	998,3	1072,3	1123,2	1281,1
① E.E.R.		3,22	3,26	3,21	3,29	3,22	3,25	3,17	3,18
① E.E.R.		2,88	3,01	2,92	3,02	2,95	3	2,89	2,91
① Absorbed power	kW	239,8	251,7	276,4	293,1	319,7	343,4	371	417,3
① Absorbed power	kW	260,2	261,9	290,2	306,8	338,4	357,4	388,7	440,2
TCAVTL-TCAVQL MODEL		2765	2815	2885	2955	21025	21105	21175	21335
② TCAVTL Sound pressure	dB(A)	67	67	68	68	68	69	69	69
② TCAVQL Sound pressure	dB(A)	58	59	60	60	60	60	61	61
③ TCAVTL Sound power	dB(A)	100	100	101	101	101	102	102	102
③ TCAVQL Sound power	dB(A)	91	92	93	93	93	93	94	94
Screw compressor/steps	n.								
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2765	2815	2885	2955	21025	21105	21175	21335
L - Width	mm	7150	8250	8250	9350	9350	10450	10450	11550
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVTL weight	kg	4860	5705	6135	6680	6745	7130	7150	7555
① TCAVQL weight	kg	5260	6105	6535	7080	7145	7530	7550	7955
SEASONAL ENERGY PERFORMANCE									
TCAVBL MODEL SEASONAL PERFORMANCE IN COOLING MODE		2755	2805	2865	2935	2995	21075	21115	21275
① Pdesignc (EN 14825)	kW	758,4	799,4	865,3	944,3	994,2	1081,3	1121,2	1287,1
① SEER (EN 14825)		4,57	4,58	4,57	4,6	4,58	4,59	4,59	4,62
② ηs,c	%	180	180	180	181	180	181	181	182
TCAVTL MODEL SEASONAL PERFORMANCE IN COOLING MODE		2765	2815	2885	2955	21025	21105	21175	21335
① Pdesignc (EN 14825)	kW	772,3	820,4	887,3	964,3	1029,3	1116,2	1176,2	1327,1
① SEER (EN 14825)		4,76	4,74	4,7	4,73	4,72	4,77	4,71	4,74
② ηs,c	%	188	186	185	186	186	188	185	186
TCAVQL MODEL SEASONAL PERFORMANCE IN COOLING MODE		2765	2815	2885	2955	21025	21105	21175	21335
① Pdesignc (EN 14825)	kW	749,3	788,4	847,3	926,4	998,3	1072,3	1123,2	1281,1
① SEER (EN 14825)		4,66	4,63	4,63	4,64	4,61	4,67	4,63	4,63
② ηs,c	%	183	182	182	182	181	184	182	182

TCAVBZ MODEL		2755	2805	2865	2935	2995	21075	21115	21275
① Nominal cooling capacity	kW	761,4	803,4	869,3	948,3	999,2	1086,3	1126,2	1293,1
① E.E.R.		2,95	3,04	2,96	3,05	2,99	3,11	3	3,12
① Absorbed power	kW	258,1	264,3	293,7	310,9	334,2	349,3	375,4	414,5
TCAVBZ MODEL		2755	2805	2865	2935	2995	21075	21115	21275
② Sound pressure	dB(A)	67,5	67,5	68	68	68	69	69	69
③ Sound power	dB(A)	100	100	101	101	101	102	102	102
Screw compressor/steps	n.								
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2755	2805	2865	2935	2995	21075	21115	21275
L - Width	mm	5990	7150	7150	8250	8250	9350	9350	10450
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVBZ weight	kg	4390	5400	5820	6210	6270	6780	6800	7180
TCAVTZ-TCAVQZ MODEL		2765	2815	2885	2955	21025	21105	21175	21335
① Nominal cooling capacity	kW	775,3	824,4	891,3	968,3	1034,3	1121,2	1181,2	1333,1
① Nominal cooling capacity	kW	752,3	791,4	851,3	930,4	1003,3	1077,3	1128,2	1287,1
① E.E.R.		3,3	3,34	3,3	3,37	3,31	3,34	3,26	3,27
① E.E.R.		2,96	3,09	3	3,09	3,03	3,07	2,96	2,98
① Absorbed power	kW	234,9	246,8	270,1	287,3	312,5	335,7	362,3	407,7
① Absorbed power	kW	254,2	256,1	283,8	301,1	331,1	350,9	381,1	431,9
TCAVTZ-TCAVQZ MODEL		2765	2815	2885	2955	21025	21105	21175	21335
② TCAVTZ Sound pressure	dB(A)	67	67	68	68	68	69	69	69
② TCAVQZ Sound pressure	dB(A)	58	59	60	60	60	60	61	61
③ TCAVTZ Sound power	dB(A)	100	100	101	101	101	102	102	102
③ TCAVQZ Sound power	dB(A)	91	92	93	93	93	93	94	94
Screw compressor/steps	n.								
Circuits	n.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		2765	2815	2885	2955	21025	21105	21175	21335
L - Width	mm	7150	8250	8250	9350	9350	10450	10450	11550
H - Height	mm	2480	2480	2480	2480	2480	2480	2480	2480
P - Depth	mm	2260	2260	2260	2260	2260	2260	2260	2260
① TCAVTZ weight	kg	4860	5705	6135	6680	6745	7130	7150	7555
① TCAVQZ weight	kg	5260	6105	6535	7080	7145	7530	7550	7955
SEASONAL ENERGY PERFORMANCE									
TCAVBZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		2755	2805	2865	2935	2995	21075	21115	21275
① Pdesignc (EN 14825)	kW	761,4	803,4	869,3	948,3	999,2	1086,3	1126,2	1293,1
① SEER (EN 14825)		4,61	4,63	4,6	4,64	4,61	4,63	4,63	4,66
② ηs,c	%	181	182	181	183	181	182	182	183
TCAVTZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		2765	2815	2885	2955	21025	21105	21175	21335
① Pdesignc (EN 14825)	kW	775,3	824,4	891,3	968,3	1034,3	1121,2	1181,2	1333,1
① SEER (EN 14825)		4,8	4,78	4,74	4,77	4,77	4,82	4,75	4,78
② ηs,c	%	189	188	187	188	188	190	187	188
TCAVQZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		2765	2815	2885	2955	21025	21105	21175	21335
① Pdesignc (EN 14825)	kW	752,3	791,4	851,3	930,4	1003,3	1077,3	1128,2	1287,1
① SEER (EN 14825)		4,69	4,67	4,66	4,66	4,64	4,69	4,66	4,66
② ηs,c	%	185	184	183	183	183	185	183	183
TCAVBL MODEL							21405	21505	
① Nominal cooling capacity	kW						1399,1	1503,2	
① E.E.R.							2,94	2,92	
① Absorbed power	kW						475,9	514,8	
TCAVBL MODEL							21405	21505	
② Sound pressure	dB(A)						70	71	
③ Sound power	dB(A)						103	104	
Screw compressor/steps	n.								
Circuits	n.						2	2	
Electrical supply	V-ph-Hz						400-3-50	400-3-50	
DIMENSIONS AND WEIGHTS							21405	21505	
L - Width	mm						11550	11550	
H - Height	mm						2480	2480	
P - Depth	mm						2260	2260	
① TCAVBL weight	kg						8560	9010	
TCAVTL-TCAVQL MODEL							21455	21565	
① Nominal cooling capacity	kW						1443,2	1557,1	
① Nominal cooling capacity	kW						1400,3	1501,2	
① E.E.R.							3,12	3,08	
① E.E.R.							2,92	2,86	
① Absorbed power	kW						462,6	505,6	
① Absorbed power	kW						479,6	524,9	
TCAVTL-TCAVQL MODEL							21455	21565	
② TCAVTL Sound pressure	dB(A)						70	71	
② TCAVQL Sound pressure	dB(A)						62	63	
③ TCAVTL Sound power	dB(A)						103	104	
③ TCAVQL Sound power	dB(A)						95	96	
Screw compressor/steps	n.								
Circuits	n.						2	2	
Electrical supply	V-ph-Hz						400-3-50	400-3-50	
DIMENSIONS AND WEIGHTS							21455	21565	
L - Width	mm						12710	12710	
H - Height	mm						2480	2480	

P - Depth	mm	2260	2260
① TCAVTL weight	kg	9390	9850
① TCAVQL weight	kg	9810	10270
SEASONAL ENERGY PERFORMANCE			
TCAVBL MODEL SEASONAL PERFORMANCE IN COOLING MODE		21405	21505
① Pdesignc (EN 14825)	kW	1399,1	1503,2
① SEER (EN 14825)		4,56	4,58
② ηs,c	%	179	180
TCAVTL MODEL SEASONAL PERFORMANCE IN COOLING MODE		21455	21565
① Pdesignc (EN 14825)	kW	1443,2	1557,1
① SEER (EN 14825)		4,74	4,72
② ηs,c	%	187	186
TCAVQL MODEL SEASONAL PERFORMANCE IN COOLING MODE		21455	21565
① Pdesignc (EN 14825)	kW	1400,3	1501,2
① SEER (EN 14825)		4,68	4,63
② ηs,c	%	184	182
TCAVBZ MODEL		21405	21505
① Nominal cooling capacity	kW	1406,1	1507,2
① E.E.R.		3,02	2,99
① Absorbed power	kW	465,6	504,1
TCAVBZ MODEL		21405	21505
② Sound pressure	dB(A)	70	71
③ Sound power	dB(A)	103	104
Screw compressor/steps	n.		
Circuits	n.	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		21405	21505
L - Width	mm	11550	11550
H - Height	mm	2480	2480
P - Depth	mm	2260	2260
① TCAVBZ weight	kg	8560	9010
TCAVTZ-TCAVQZ MODEL		21455	21565
① Nominal cooling capacity	kW	1450,2	1564,1
① Nominal cooling capacity	kW	1407,3	1502,2
① E.E.R.		3,19	3,16
① E.E.R.		3	2,92
① Absorbed power	kW	454,6	495
① Absorbed power	kW	469,1	514,5
TCAVTZ-TCAVQZ MODEL		21455	21565
② TCAVTZ Sound pressure	dB(A)	70	71
② TCAVQZ Sound pressure	dB(A)	62	63
③ TCAVTZ Sound power	dB(A)	103	104
③ TCAVQZ Sound power	dB(A)	95	96
Screw compressor/steps	n.		
Circuits	n.	2	2
Electrical supply	V-ph-Hz	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS		21455	21565
L - Width	mm	12710	12710
H - Height	mm	2480	2480
P - Depth	mm	2260	2260
① TCAVTZ weight	kg	9390	9850
① TCAVQZ weight	kg	9810	10270
SEASONAL ENERGY PERFORMANCE			
TCAVTZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		21405	21505
① Pdesignc (EN 14825)	kW	1406,1	1507,2
① SEER (EN 14825)		4,6	4,6
② ηs,c	%	181	181
TCAVTZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		21455	21565
① Pdesignc (EN 14825)	kW	1450,2	1564,1
① SEER (EN 14825)		4,79	4,76
② ηs,c	%	189	188
TCAVQZ MODEL SEASONAL PERFORMANCE IN COOLING MODE		21455	21565
① Pdesignc (EN 14825)	kW	1407,3	1502,2
① SEER (EN 14825)		4,71	4,66
② ηs,c	%	186	183

Data at the following conditions:

- ① Air: 35°C - Water: 12/7°C.
 - ② In open field (Q = 2) at 10 m from the unit.
 - ③ Total sound power level in dB(A) based on measurements carried out in accordance with regulation UNI EN-ISO 9614.
 - ④ Weight referred to the unit without load and not accessorised.
 - TCAVQL super-silenced versions.
Performance according to EN 14511.
 - ① Low temperature application (7°C)
 - ② Seasonal energy efficiency: low temperature cooling (EU Regulation 2016/2281)
- Data at the following conditions:
- ① Air: 35°C - Water: 12/7°C.
 - ② In open field (Q = 2) at 10 m from the unit.
 - ③ Total sound power level in dB(A) based on measurements carried out in accordance with regulation UNI EN-ISO 9614.
 - ④ Weight referred to the unit without load and not accessorised.
 - TCAVQZ super-silenced versions.
Performance according to EN 14511.
 - ① Low temperature application (7°C)

RHOSS S.P.A. declines all responsibility for possible mistakes in this document and reserves the right to alter the features of their products without notice.

Rhoss S.p.A.
Via Oltre Ferrovia, 32
33033 Codroipo (UD) - italy
tel. +39 0432 911611 - rhoss@rhoss.it
www.rhoss.it www.rhoss.com



RhossOfficial



RhossOfficialChannel



Rhoss